



HRN EN 934-4:2009

12

1020

## IZJAVA O SVOJSTVIMA

Temeljem dodatka III Uredbe (EU) 305/2011

### Intraplast® EP

02	03	01	01	002	0	000004	1180
----	----	----	----	-----	---	--------	------

#### 1. Tip proizvoda:

Jedinstveni identifikator tipa proizvoda:

Intraplast® EP

**2. Tip** broj šarže ili serijski broj ili bilo koji drugi element koji omogućava identifikaciju građevnog proizvoda temeljem članka 11 (4):

EP

Broj šarže: otisnut na pakiranju

**3. Namjeravana upotreba** ili upotrebe građevnog proizvoda, u skladu s primjenjivom usklađenom tehničkom specifikacijom, kako je predviđeno od strane proizvođača:

**Prašasti dodatak za injektiranje. Zadovoljava zahtjeve za dodatke za injektiranje i prednapinjanje prema HRN EN 934-4:2009. Odgovara zahtjevima Anexa ZA Tabela ZA.1.**

**4. Ime, registrirani trgovački naziv** ili registrirana trgovačka marka i kontakt adresa proizvođača, kako se zahtijeva u Članku 11(5):

Intraplast®

Sika CZ s.r.o.  
Bystrcka 1132/36  
CZ-624 00 Brno  
Češka

#### 5. Kontakt adresa:

Kada je primjenjivo, ime i kontakt adresa ovlaštenog predstavnika čije ovlasti pokrivaju zadatke specificirane u Članku 12(2):

**Nije primjenjivo** (vidjeti u točki 4)

#### 6. AVCP:

Sustav ili sustavi ocjenjivanja i provjere stalnosti svojstava građevnog proizvoda utvrđeno u Anexu V:

**Sustav 2+**

#### 7. Prijavljeno tijelo:

U slučaju kada je Izjava o Svojstvima (DoP) koja se odnosi na predmetni proizvod pokrivena usklađenom normom:

**HRN EN 934-2:2009, Sustav 2+:**  
Prijavljeno tijelo za certificiranje tvorničke kontrole proizvodnje br. **1020** provelo je početno ispitivanje proizvodnog pogona i proizvodnog procesa za sustav 2+, kao i stalni nadzor, procjena i ocjenjivanje tvorničke kontrole proizvodnje, te je izdan **Certifikat o sukladnosti kontrole tvorničke proizvodnje 1020-CPR-020027779.**

#### 8. Prijavljeno tijelo (ETA):

U slučaju Izjave o svojstvima građevnog  
proizvoda izdane temeljem Europskog  
Tehničkog Dopuštenja:

**Nije primjenjivo** (vidjeti u točki 7)

#### 9. Deklarirana svojstva

Bitne karakteristike	Svojstvo	Norma	Usklađena tehnička specifikacija
Tečnost 30 minuta nakon miješanja	$\leq 25s$	HRN EN 445	HRN EN 934-4:2010
Tlačna čvrstoća	$\geq 30$ nakon 28 dana	HRN EN 445	
Izdvajanje vode	$\leq 2\%$ nakon 3 sata	HRN EN 445	
Promjena obujma nakon 24 sata	$0\% \leq S \leq 5\%$	Annex B	
Opasni sastojci	Proučiti Sigurnosno tehnički list proizvoda	_____	

## 10. Izjava

Karakteristike proizvoda navedenog u točkama 1 i 2 u skladu su s Deklariranim svojstvima u točki 9. Izjava o svojstvima izdana je s punom odgovornošću proizvođača navedenog u točki 4.

Potpisano za i u ime proizvođača od:

Kontrola kvalitete i EHS:



Ing. Jaroslav Leischner  
QMS and EHS Manager

Generalni Direktor (Sika CZ):

Name: Ing. Andrej Šišolák

Position: General Manager SIKAZ, s.r.o.



Brno, 01. Svibanj 2015.

---

## Zdravstvene i sigurnosne informacije (REACH)

Za informacije i savjete o sigurnom rukovanju, skladištenju i uklanjanju kemijskih proizvoda korisnicima se preporučuje konzultirati najnoviji Sigurnosno-tehnički list proizvoda u kojem su sadržani fizikalni, ekološki, toksikološki i drugi podaci o sigurnosti.

---

---

### Pravne napomene:

Podaci i, posebice, preporuke koje se odnose na primjenu i krajnje korištenje Sika® proizvoda, dani su u dobroj vjeri temeljem sadašnjih znanja i iskustava Sika®-e za proizvode koji su pravilno skladišteni, korišteni i primijenjeni pod normalnim uvjetima u skladu sa Sika®-inim preporukama. U naravi, razlike u materijalu, podlozi i stvarnim uvjetima primjene su takve da nema jamstva u odnosu na mogućnost prodaje ili pogodnosti proizvoda za određenu namjenu, niti ikakva odgovornost može nastati temeljem bilo kakvog zakonskog odnosa, temeljem zaključaka na osnovi ovih podataka ili bilo kakvih pismenih preporuka ili bilo kakvog drugog ponuđenog savjeta. Korisnik proizvoda mora ispitati prikladnost proizvoda za namjeravanu primjenu i svrhu. Sika® zadržava pravo promjene karakteristika njenih proizvoda. Vlasnička prava trećih strana moraju se razmotriti. Sve narudžbe se prihvaćaju na osnovu naših važećih uvjeta prodaje i isporuke. Za odabrani proizvod, korisnici trebaju uvijek koristiti naše posljednje izdanje Tehničkog lista proizvoda, čiju kopiju mogu dobiti na zahtjev.

---



Za dodatne informacije  
Sika Croatia d.o.o.  
Puškarićeva 77a  
10250 Lučko – Zagreb  
Hrvatska

Tel +385 1 6594 240  
Fax +385 1 6594 241  
www.sika-croatia.hr

# DECLARATION OF PERFORMANCE

## Intraplast®-EP

EN 934-4:2009

12

1020

02	03	01	01	002	0	000004	1180
----	----	----	----	-----	---	--------	------



<b>1</b>	<b>UNIQUE IDENTIFICATION</b> of the product-typ:	<b>Intraplast®-EP</b> Batch No. see packaging
<b>2</b>	<b>INTENDED USE</b> or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	Injection aid admixture - corresponding to the basic performance requirements of EN 934-4:2009 Conforming to the Table ZA.1.
<b>3</b>	<b>MANUFACTURER</b> registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):	Intraplast® Sika CZ, s.r.o. Bystrcká 1132/36 CZ-624 00 Brno
<b>4</b>	<b>AVCP</b> System or systems of assessment and verification of constancy of performance (AVCP) or the construction product as set out in CPR, Annex V:	System 2+
<b>5</b>	<b>HARMONISED STANDARDS</b> In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:	EN 934-4:2009
<b>6</b>	<b>NOTIFIED BODY</b>	Notified factory production control certification body No. 1020 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control (FPC) 020027779.

**Declaration of Performance**

Intraplast®-EP

01.05.2015, Version no. 01

Identification nr. 02 03 01 01 002 0 000004 1180

## 7 DECLARED PERFORMANCE

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Fluidity 30 minutes after mixing	≤25 s	EN 445	
Compressive strength	≥ 30 after 28 days	EN 445	EN 934-4: 2009
Water separation	≤ 2% after 3 hod	EN 445	
Volume change after 24 hours	0% ≤ S ≤ 5%	Annex B	

NPD – no performance determined

## 8 APPROPRIATE TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Ing. Jaroslav Leischner  
Position: Quality and EHS Manager



Brno, 01.05.2015

Name: Ing. Andrej Šišolák  
Position: General Manager SIKA CZ, s.r.o.



Brno, 01.05.2015

## REACH INFORMACE

European Community Regulation on chemicals and their safe use (REACH: EC 1907/2006)

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation, or on the candidate list published by the European Chemicals Agency in concentrations above 0.1% (w/w).

## ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data. They can be downloaded at [www.cz.sika.com](http://www.cz.sika.com) or directly requested at Sika.

## LEGAL NOTE

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.


### Declaration of Performance

Intraplast®-EP

01.01.2015, Version no. 01

Identification nr. 02 03 01 01 002 0 000004 1180

**9 CE MARK**

	
<b>Sika CZ, s.r.o., Bystrcká 1132/36, 624 00 Brno</b> <b>Factory 1180</b> <b>14</b> <b>02 03 01 01 002 0 000004 1180</b> <b>EN 934-4: 2009</b>	
Injection aid admixture - corresponding to the basic performance requirements of EN 934-4:2009 Conforming to the Table ZA.1.	
<b>Essential characteristics</b>	<b>Performance</b>
Fluidity 30 minutes after mixing	≤25 s
Compressive strength	≥ 30 MPa after 28 days
Water separation	≤ 2% after 3 hod
Volume change after 24 hours	0% ≤ S ≤ 5%

**For more information contact:**

Sika CZ, s.r.o., Bystrcká 1132/36, CZ 624 00 Brno  
tel: +420 546 422 464  
Fax: +420 546 422 400  
E-mail: sika@cz.sika.com

**Declaration of Performance**

Intraplast®-EP  
01.01.2015, Version no. 01  
Identification nr. 02 03 01 01 002 0 000004 1180