



HRN EN 13813:2002

15

IZJAVA O SVOJSTVIMA

Temeljem dodatka III Uredbe (EU) 305/2011

Sika® Screed-100

02	13	04	03	100	0	000034	1180
----	----	----	----	-----	---	--------	------

1. Tip proizvoda:

Jedinstveni identifikator tipa proizvoda:

Sika® Screed-100

2. Tip broj šarže ili serijski broj ili bilo koji drugi element koji omogućava identifikaciju građevnog proizvoda temeljem članka 11 (4):

Screed-100

Broj šarže: otisnut na pakiranju

3. Namjeravana upotreba ili upotrebe građevnog proizvoda, u skladu s primjenjivom usklađenom tehničkom specifikacijom, kako je predviđeno od strane proizvođača:

Samoizravnavajući cementni estrih za unutarnju uporabu

U skladu s HRN EN 13813 CT-C40-F6

4. Ime, registrirani trgovački naziv ili registrirana trgovačka marka i kontakt adresa proizvođača, kako se zahtijeva u Članku 11(5):

Sika®

Sika CZ s.r.o.
Bystrcka 1132/36
CZ-624 00 Brno
Češka

5. Kontakt adresa:

Kada je primjenjivo, ime i kontakt adresa ovlaštenog predstavnika čije ovlasti pokrivaju zadatke specificirane u Članku 12(2):

Nije primjenjivo (vidjeti u točki 4)

6. AVCP:

Sustav ili sustavi ocjenjivanja i provjere stalnosti svojstava građevnog proizvoda utvrđeno u Anex-u V:

Sustav 4 (HRN EN 13813:2002)

7. Prijavljeno tijelo:

U slučaju kada je Izjava o Svojstvima (DoP) koja se odnosi na predmetni proizvod pokrivena usklađenom normom:

Nije primjenjivo

Izjava o svojstvima



8. Prijavljeno tijelo (ETA):

U slučaju Izjave o svojstvima građevnog
proizvoda izdane temeljem Europskog
Tehničkog Dopuštenja:

Nije primjenjivo (vidjeti u točki 7)

9. Deklarirana svojstva

--	--	--	--

Bitne karakteristike	Svojstvo	Norma	Usklađena tehnička specifikacija
Emisija korozivnih supstanci (cement)	NPD	HRN EN 13813	HRN EN 13813: 2002
Otpornost na habanje	NPD	HRN EN 13892-5	
Prionjivost	NPD	HRN EN 13892-8	
Otpornost na udarce	NPD	HRN EN ISO 6272	
Paropropusnost	NPD	HRN EN ISO 7783-2	
Zvučna izolacija	NPD	HRN EN ISO 140-1	
Apsorpcija zvuka	NPD	HRN EN ISO 354	
Reakcija na požar	A1	HRN EN 13501-1	
Termička otpornost	NPD	HRN EN 12664	
Kemijska otpornost	NPD	HRN EN 13529	
Tlačna čvrstoća	C40	HRN EN 13892-2	
Savojna čvrstoća	F6	HRN EN 13892-2	

10. Izjava

Karakteristike proizvoda navedenog u točkama 1 i 2 u skladu su s Deklariranim svojstvima u točki 9. Izjava o svojstvima izdana je s punom odgovornošću proizvođača navedenog u točki 4.

Potpisano za i u ime proizvođača od:

Kontrola kvalitete EHS:



Ing. Jaroslav Leischner
Manažer kvaliteta EMS

Generalni Direktor:

Name: Ing. Andrej Šišolák
Position: General Manager SIKA CZ, s.r.o.



Brno, 01.05.2015

Brno, 01. Svibanj 2015.

Zdravstvene i sigurnosne informacije (REACH)

Za informacije i savjete o sigurnom rukovanju, skladištenju i uklanjanju kemijskih proizvoda korisnicima se preporučuje konzultirati najnoviji Sigurnosno-tehnički list proizvoda u kojem su sadržani fizikalni, ekološki, toksikološki i drugi podaci o sigurnosti.

Pravne napomene:

Podaci i, posebice, preporuke koje se odnose na primjenu i krajnje korištenje Sika® proizvoda, dani su u dobroj vjeri temeljem sadašnjih znanja i iskustava Sika®-e za proizvode koji su pravilno skladišteni, korišteni i primijenjeni pod normalnim uvjetima u skladu sa Sika®-inim preporukama. U naravi, razlike u materijalu, podlozi i stvarnim uvjetima primjene su takve da nema jamstva u odnosu na mogućnost prodaje ili pogodnosti proizvoda za određenu namjenu, niti ikakva odgovornost može nastati temeljem bilo kakvog zakonskog odnosa, temeljem zaključaka na osnovi ovih podataka ili bilo kakvih pismenih preporuka ili bilo kakvog drugog ponuđenog savjeta. Korisnik proizvoda mora ispitati prikladnost proizvoda za namjeravanu primjenu i svrhu. Sika® zadržava pravo promjene karakteristika njenih proizvoda. Vlasnička prava trećih strana moraju se razmotriti. Sve narudžbe se prihvaćaju na osnovu naših važećih uvjeta prodaje i isporuke. Za odabrani proizvod, korisnici trebaju uvijek koristiti naše posljednje izdanje Tehničkog lista proizvoda, čiju kopiju mogu dobiti na zahtjev.



Za dodatne informacije
Sika Croatia d.o.o.
Puškarićeva 77a
10250 Lučko – Zagreb
Hrvatska

Tel +385 1 6594 240
Fax +385 1 6594 241
www.sika-croatia.hr

DECLARATION OF PERFORMANCE

Sika® Screed-100

EN 13813: 2002

15



02	13	04	03	100	0	000034	1180
----	----	----	----	-----	---	--------	------

1	UNIQUE IDENTIFICATION of the product-typ:	Sika® Screed-100 Batch No. see packaging
2	INTENDED USE or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	1-component, self-leveling cementitious screed material and floor screed for interior use corresponding to the basic performance requirements of EN 13813:2002. Thickness layer from 10-60 mm: CT-C40-F6. Conforming to the Annex ZA, Table ZA.1.1 a ZA.3.2
3	MANUFACTURER registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):	Sika® Sika CZ, s.r.o. Bystrcká 1132/36 CZ-624 00 Brno
4	AVCP System or systems of assessment and verification of constancy of performance (AVCP) or the construction product as set out in CPR, Annex V:	EN 13813: System 4
5	HARMONISED STANDARDS	EN 13813: 2002
6	NOTIFIED BODY In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:	The producer set up the factory production control of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of the factory production control.

Declaration of Performance

Sika® Screed-100

01.05.2015, Version no. 01

Identification nr. 02 13 04 03 100 0 000034 1180

7 DECLARED PERFORMANCE

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Release of dangerous substances	Pass	-	EN 13813:2002
Release of corrosive substances	cement	-	
Water permeability	NPD	EN 1062-3	
Water vapour permeability	NPD	EN 12086	
Compressive strength	C40	EN 13892-2	
Flexural strength	F6	EN 13892-2	
Wear resistance	NPD	EN 13892-4	
Bond strength	NPD	EN 13892-8	
Sound insulation	NPD	EN 140-6	
Sound absorption	NPD	EN 12354-6	
Thermal resistance	NPD	EN 12664	
Chemical resistance	NPD	EN 13529	
Reaction to fire	A1	EN 13501	
Radionuclide content	Pass	index I ≤ 1	Evaluation according to regulation 307/02 Sb.

NPD – not performance declared

8 APPROPRIATE TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Ing. Jaroslav Leischner
Position: Quality and EHS Manager



Brno, 01.05.2015

Name: Ing. Andrej Šišolák
Position: General Manager SIKA CZ, s.r.o.



Brno, 01.05.2015

REACH INFORMACE

European Community Regulation on chemicals and their safe use (REACH: EC 1907/2006)

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet.

Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation, or on the candidate list published by the European Chemicals Agency in concentrations above 0.1% (w/w).

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data. They can be downloaded at www.cz.sika.com or directly requested at Sika.

Declaration of Performance

Sika® Screed-100


01.01.2015, Version no. 01

Identification nr. 02 13 04 03 100 0 000034 1180

LEGAL NOTE

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

9 CE MARK

	
Sika CZ, s.r.o., Bystrcká 1132/36, 624 00 Brno Výrobní závod 1180 15 02 13 04 03 100 0 000034 1180 EN 13813:2002	
1-component, self-leveling cementitious screed material and floor screed for interior use corresponding to the basic performance requirements of EN 13813:2002. Thickness layer from 10-60 mm: CT-C40-F6. Sika® Screed-100	
Essential characteristics	Performance
Reaction to fire	A1 _{fl}
Release of corrosive substances	CT
Compressive strength	C40
Flexural strength	F6
Adhesion strength	NPD
Impact resistance	NPD
Sound insulation	NPD
Sound absorption	NPD
Thermal resistance	NPD
Chemical resistance	NPD
Water permeability	NPD
Wear resistance	NPD
Bond strength	NPD

For more information contact:

Sika CZ, s.r.o., Bystrcká 1132/36, CZ 624 00 Brno
tel: +420 546 422 464
Fax: +420 546 422 400
E-mail: sika@cz.sika.com

Declaration of Performance

Sika® Screed-100
01.01.2015, Version no. 01
Identification nr. 02 13 04 03 100 0 000034 1180